BIO-DEHYDRATORS

HGF-450ML



MODEL: HGF-450ML

Make food waste easy to process with our biodehydrator. Use it as a soil amendment, send it to a compost facility, or dispose of it responsibly.

Load your food waste into the machine where it is macerated and heated to a point where the moisture is extracted from the reactor drum. The machine then condenses the steam and discharges a clear water condensate (no total suspended solids!). The remaining dry output is 80-90% volume-reduced, inert, pathogen free, compostable product with a variety of uses.

450lbs [200kg] capacity of food waste per cycle.

This is great for medium-sized operators such as corporate cafeterias, colleges, and larger commercial kitchens. Average cycle times are 13-18 hours depending on the moisture content. Single button operation.

CAPACITY:	450lbs / 200kg (per cycle)
LENGTH:	57.18in / 1452mm
DEPTH:	46.55in / 1182mm
HEIGHT:	47.53in / 1207mm
CYCLE TIME:	13-18 hours

Note: figures may vary due to psychromatrics as air density (height above sea level), air temperature, humidity etc.

Note: Specifications of all models may be changed without prior notice

- ** Approximate capacity daily and capacity per cycle is a range and not to be construed as an exact calculation as the bio reactor drums are a fixed volume, but density and moisture content of food waste varies.
- * 1CMM = 1CFM * 35.3/ 1CMM = 35.3CFM

Processing up to 13,500 lbs [6 tons] p/m



MODEL	HGF-450ML	
Cycle Times/Full Load (capacity per cycle)**	1 Cycle / 13-18hrs 450lbs / 200kg	
Possible Cycles Per Day**	1-1.5 Cycle	
Approximate Capacity per day (full 24 hours) **	560lbs / 250kg	
NOTE: CYCLE TIME WILL VARY FROM LOAD TO LOAD DEPENDING ON THE MOISTURE CONTENT OF THE FOOD WASTE		
Depth	46.55in / 1182mm	
Length/Width	57.18in / 1452mm	
Length/Width W/Lift	NO LIFT	
Height	47.53in / 1207mm	
Height W/Lift	NO LIFT	
External Radiator Size (L x W x H)	Х	
Drum Volume	92.46gal / 350Liters	
Net weight of unit	1325lbs / 600kg	
CFM output radiator	1200.2CFM = 34CMM	
Delta T	86F / 30c	
BTU/hr = 1.08 x CFM x ΔT	111475	
Converted to kW	32.7	

